



# ROAD SAFETY SIGNS

## 33. ROAD SIGNS CONFORMING TO IRC : 67-2012 STANDARD

(a)



(b)



(c)



### Specifications

|                                      |  |
|--------------------------------------|--|
| Substrate:                           | 2mm thick Aluminium Sheet with degreasing treatment & fine grinding on front side for proper pasting of Reflective sheet & degreasing treatment & stove enamel paint on backside. or 3mm thick ACP (Aluminium Composite Panel) |
| Reflective Material                  | * Engineering Grade/Safety Grade<br>* High Intensity Grade (Encapsulated Lens type)<br>* High Intensity Prismatic <b>HIP</b><br>* Micro prismatic Lens (Diamond Grade/OMNI Grade Type VIII & IX)                               |
| Symbols/Messages / Lettering/Border: | Screen Printed/Cut-outs.   |

### Sizes of Signs

| Signs                        | Shape                | Normal Size (mm) | Small Size (mm) |
|------------------------------|----------------------|------------------|-----------------|
| Mandatory                    |                      |                  |                 |
| i) Stop Sign                 | Octagonal            | 900              | 900             |
| ii) Give way sign (Inverted) | Equilateral triangle | 900              | 600             |
| ii) Others                   | Circular             | 600              | 400             |
| Warning                      | Equilateral Triangle | 900              | 600             |
| Informatory                  | Rectangle            | 800x600          | 600x450         |

**ROAD FURNITURE & ACCESSORIES**  
EASY CHOICE FOR SIGNS, MADE YOUR WAY-FAST

